

## Bounty

<b>Tuft gauge</b>	5/64 cut pile		ISO 2424
<b>Pilecomposition</b>	100% PES		ISO 2424
<b>Primary Backing</b>	Woven		ISO 2424
<b>Secondary backing</b>	Duo Backing		ISO 2424
<b>Width</b>	400 cm, 500 cm	± 1%	EN 986
<b>Pile Weight</b>	1650 gr/m <sup>2</sup>		ISO 8543
<b>Total weight</b>	2500 gr/m <sup>2</sup>	± 15%	ISO 8543
<b>Pile height</b>	11 mm		ISO 1765
<b>Total Height</b>	13 mm		ISO 1765
<b>Number of knots</b>	277.750/m <sup>2</sup>	-7.5% .+10%	ISO 1763
<b>Fire Classification</b>	Cfl-S1		EN 13501-1
<b>Use Area</b>	Heavy domestic use (23)		EN 1307
<b>GUT Nr.</b>	AB099C55 GUT		www.pro-dis.info
<b>Thermal resistance</b>	Ca. 0,0135 M <sup>2</sup> KW		ISO 8302
<b>Light fastness</b>	≥ 5		105-B02
<b>Wearebility</b>	≥ 4		105-X12
<b>Water fastness</b>	≥ 4		105-E01
<b>Comments</b>	Micropes		

## Floorsymbols



## Certificates

