

## Carrera

<b>Tuft gauge</b>	1/10 cut pile		ISO 2424
<b>Pilecomposition</b>	100% PES		ISO 2424
<b>Primary Backing</b>	Woven		ISO 2424
<b>Secondary backing</b>	Comfortbacking		ISO 2424
<b>Width</b>	400 cm	± 1%	EN 986
<b>Pile Weight</b>	2650 gr/m <sup>2</sup>		ISO 8543
<b>Total weight</b>	Comfortbacking : 3350 gr/m <sup>2</sup>	± 15%	ISO 8543
<b>Pile height</b>	12 mm		ISO 1765
<b>Total Height</b>	Comfortbacking : 14 mm		ISO 1765
<b>Number of knots</b>	205.400/m <sup>2</sup>	-7.5% .+10%	ISO 1763
<b>Fire Classification</b>	Cfl-S1		EN 13501-1
<b>Use Area</b>	Heavy domestic use (23)		EN 1307
<b>Thermal resistance</b>	0,1 M <sup>2</sup> KW		ISO 8302
<b>Light fastness</b>	≥ 5		105-B02
<b>Wearebility</b>	≥ 4		105-X12
<b>Water fastness</b>	≥ 4		105-E01

## Floorsymbols



## Certificates



2018  
 Condor Carpets  
 Euroweg 3  
 8061 SB Hasselt  
 EN1307  
 DOP: C-025TC196  
 Reaction to fire:  
 Cfl-s1  
 1658  
 Slip resistance: DS  
 Resilient floor  
 covering to be  
 used within a  
 building



**Intenza**  
 the ultimate in soft carpets

